



Rated Voltage	45kV
Rated Current	800A
Impulse withstand Phase-Earth	250kV
Impulse withstand over isolating distance	290kV
Power frequency withstand phase-earth 1 min wet	95kV
Power frequency withstand voltage over isolating distance 1 min wet	110kV
Duration of short time current	3s
Peak current	25 kA
Insulator material	Silicon rubber
Insulator creepage distance	1055mm
Characteristic	Value
TECHNICAL CHARACTERISTICS	

Toleranser/Tolerances
 ISO 2768-v (mycket grov/very coarse)
 Om inget annat anges/ If nothing else stated

© AB GEVEA
 Box 12043
 60012 Norrköping
 SWEDEN
 Tel. +46 11 184800
 Fax. +46 11 182350
 WWW.GEVEA.COM

REVISION HISTORY				
ZONE	REV	DESCRIPTION	DATE	APPROVED
	1	Byte av stångstöd till 9338	2015-10-16	SZ
Konstruerad av/Designed by		Datum/Date	Vikt/Weight	Material/Material
Fredrik Karlsson		2014-03-19	N/A	N/A
Ytbeh/Surf. Trea.				N/A
Ritnings Nr/Drawing Nr				8020
Skala/Scale			Version/Revision	
1:20			A	



25F-1OUT-H
 25kV 800A